

TITAN HOOKLOADER

Hyva Titan Hookloaders are designed for daily use in rugged environments and are well known for their reliability and low maintenance. Aimed at the medium to heavy truck classes the Titan hookloader can handle a wide variety of loads and containers. Further enhancing Hyva's track record for innovation and versatility, available today with over 10,000 units working in more than 60 countries globally. Due to the extended range of advanced features and benefits, hookloader operation is now faster, safer, more efficient, and more productive than ever.

Titan. For work without limit



MODEL RANGE

Description	Models													
	T13-114-S		T13-134-S		T22-134-S		T22-150-S		T22-161-S		T22-189-S		T22-201-S	
Lifting & Tipping Capacity (lbs)	13,000		13,000		22,000		22,000		22,000		22,000		22,000	
Container Length Range (ft)	10 to 12		11 to 14		11 to 14		10 to 15		11 to 16		12 to 18		12 to 19	
Optimum Container Length (ft)	12		14		13		14		15		17		18	
Approx. System Weight (lbs)	1,782		1,978		2,557		2,683		2,751		2,992		3,071	
L - System Length (in)	114.3		134.0		134		150		161		189		201	
Lb - Overall Length (in)	128.1		147.5		155.9		165.7		175.6		197.2		207.1	
H - Hook Heights (in)	36	54	36	54	36	54	36	54	36	54	54	54	54	54
C - Frame Ext from Mast (in)	6.7	6.7	6.3	6.3	18.7	17.7	12.8	11.8	10.9	9.8	0.8	0	0	0
Ds - Lowest Hook Height (in)	31.4	29.9	31.1	29.9	28.4	31.6	28.8	30.6	29.4	31.1	46.3	47	47	47
K - Dump Angle (degrees)	50	50	58	58	49	47	49	48	49	48	48	48	48	48
X - Mast Travel (in)	21.7	21.7	31.5	31.5	23.6	17.7	31.4	25.5	35.4	29.5	47.3	51.2	51.2	51.2

HIGHLIGHTS



Subframe support brackets



Main cylinders



Reduced height




Zinc-plated container support



Exchangeable hooks



Corrosion resistant paint



Fast Offload



Electronic Control System (IQAN)

GODWIN BODIES



All Godwin hookloader bodies are manufactured using minimum ASTM mill certified grade 50 steel or greater. Godwin bodies are also zinc primed and powder coated tough for the highest standard corrosion protection in the industry.

Phone: 800-892-0181 Fax: 910-892-7402
www.godwinmfg.com

